

**Article:** 030FAP**Description:** ELEMENTO DI CONTATTO NO PROTETTO**Color:** VERDE**Nomenclature:** 85365080

<b>DATA SHEET</b>	
<b>Approvals</b>	CE, UL, CSA
<b>Compliance with standards</b>	EN-IEC60947-1, EN-IEC60947-5-1, UL508, CSA C22-2
<b>Working Temperatures</b>	-25° ÷ +65°C
<b>Protection degree</b>	IP20 (EN-IEC60529) with 030PFA - 030PFC
<b>Mechanical durability</b>	5.000.000 Operations
<b>Rated insulation voltage</b>	Ui 690V - Uimp 4KV (IEC-EN 60947-1)
<b>Electrical ratings</b>	AC15-DC13 (EN-IEC 60947-5-1) - A600-P300 (UL 508)
<b>AC Performances</b>	AC 24V-10A, 120V-6A, 240V-3A, 600V-1,2A
<b>DC Performances</b>	DC 24V-5A, 120V-1,1A, 240V-0,55A
<b>Rated thermal current</b>	Ith 10A (EN-IEC 60947-1)
<b>Contact movement</b>	Slow action contact
<b>Contacts</b>	Self cleaning by pads creeping
<b>NC Contact</b>	Positive opening function
<b>Housing material</b>	PC Polycarbonate
<b>Contact material</b>	Ag 1000/1000
<b>Terminal screws material</b>	Zinc plated steel
<b>Terminal screws</b>	Combined head flat blade and Ph2 Tightening torque 0.8÷1 Nm
<b>Cable lugs</b>	Fork tupe "springer spade" model